Advanced Broadband Acoustic Clutter

Charles W. Holland

The Pennsylvania State University
Applied Research Laboratory
P.O. Box 30, State College, PA 16804-0030
Phone: (814) 865-1724 Fax (814) 863-8783 email: holland-cw@psu.edu

Grant Number: N00014-08-1-0098
1 Nov 2007 – 31 Oct 2010

ABSTRACT

The performance of active sonar systems in littoral environments is often limited by discrete clutter and diffuse bottom reverberation. Discrete clutter tends to be nearly ubiquitous, but its characteristics have been difficult to predict. It has also been difficult to predict the frequency and angular dependence of the seabed scattering strength, which is important for predicting the time dependence of the background reverberation upon which the clutter highlights are distributed. New measurement techniques were developed that have promising possibilities for use in the survey community including quantifying scattering strength frequency and angular dependence, localizing/quantifying clutter discrete scattering, and quantifying seabed reflection which is important for prediction of reverberation, clutter and target echo structure. In addition to measurement techniques modeling advances were made for rapid calculation of clutter and target echo, and a deeper understanding of the impact of seabed range dependence on propagation and clutter.

LONG TERM GOALS

The long term goal is to improve performance of low-mid frequency active sonar systems against clutter.

OBJECTIVES

The objectives are to identify/understand the mechanisms that lead to clutter and develop models that predict the temporal/spatial/frequency dependence of the observed clutter and background diffuse reverberation.

APPROACH

The experimental approach was based upon exploiting both long-range observations of clutter and short-range, or direct-path observations (seabed scattering and reflection) of the features that give rise to the clutter. Direct path observations offer two significant advantages: a) the uncertainties associated with propagation (through a generally sparsely sampled ocean) are minimized, and b) the measurement

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1. REPORT DATE *(DD-MM-YYYY)*	2. REPORT TYPE	3. DATES COVERED *(From - To)*
28-01-2011	Final Report	1-Nov 2007 to 31 Oct 2010

4. TITLE AND SUBTITLE
Advanced Broadband Acoustic Clutter Project

5a. CONTRACT NUMBER

5b. GRANT NUMBER
N000-14-08-1-0098

5c. PROGRAM ELEMENT NUMBER

6. AUTHOR(S)
Charles W. Holland

5d. PROJECT NUMBER
15251

5e. TASK NUMBER
01

5f. WORK UNIT NUMBER
06110

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)
Applied Research Laboratory
The Pennsylvania State University
P. O. Box 30
State College, PA 16804-0030

8. PERFORMING ORGANIZATION REPORT NUMBER

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)
Davis B. Reeder
Office of Naval Research
875 North Randolph Street
Arlington, VA 22203-1995

10. SPONSOR/MONITOR'S ACRONYM(S)
ONR

11. SPONSORING/MONITORING AGENCY REPORT NUMBER

12. DISTRIBUTION AVAILABILITY STATEMENT
Approved for Public Release; distribution is Unlimited

13. SUPPLEMENTARY NOTES
N/A

14. ABSTRACT
The performance of active sonar systems in littoral environments is often limited by discrete clutter and diffuse bottom reverberation. Discrete clutter tends to be nearly ubiquitous, but its characteristics have been difficult to predict. It has also been difficult to predict the frequency and angular dependence of the seabed scattering strength, which is important for predicting the time dependence of the background reverberation upon which the clutter highlights are distributed. New measurement techniques were developed that have promising possibilities for use in the survey community including quantifying scattering strength frequency and angular dependence, localizing/quantifying clutter discrete scattering, and quantifying seabed reflection which is important for prediction of reverberation, clutter and target echo structure. In addition to measurement techniques modeling advances were made for rapid calculation of clutter and target echo, and a deeper understanding of the impact of seabed range dependence on propagation and clutter.

15. SUBJECT TERMS
reverberation, clutter, seabed scattering, acoustic modeling, measurements

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			5Charles W. Holland
Unclassified	Unclassified	Unclassified	Unlimited		19b. TELEPONE NUMBER *(Include area code)* 814-865-1724

geometries are favorable to producing data from which hypotheses about the scattering mechanisms can be directly tested. The theoretical approach for reverberation, clutter and target echo structure was based in part on energy flux methods.

RESULTS

The results have been extensively reported in the peer-reviewed literature and in conferences and symposia (see references below). A summary of key advances are listed below.

Modeling/analysis:

- Developed a simple theory for propagation in a waveguide with range-dependent seabed properties (Refs [1,12]). The importance of the theory is that it provides some deep insights into the effects of range-dependence on propagation. This in turn has lead to some deep insights into seabed variability on clutter (late in the project and hence to date unpublished).
- Developed high-fidelity clutter and target echo model that is computationally very efficient, faster than rays or normal modes (Ref [13]). The efficiency makes it attractive for potential use in simulation.
- Advanced the understanding (with modeling and measurements) of reverberation and clutter from sub-bottom interfaces (Refs [2, 7, 18]). Key result: despite some claims to the contrary in the ocean acoustics community, sub-bottom clutter can and does occur in shallow water environments. Detailed analyses illuminates the relation between the frequency and angle dependence of reflection, scattering, reverberation, propagation, and clutter in both theory and measurements. This is important because in some shallow water areas (especially those with significant riverine deposition) the reverberation and clutter may be controlled by sub-bottom mechanisms.
- Analyzed clutter data from bottomed shipwreck (with Doug Abraham, data from Clutter'07 Experiment) to examine dependence of clutter statistics on multipath (Ref [8]). Key result: in the shallow water environment on the Malta Plateau both modeled and measured statistics showed weak dependence on multipath. This can potentially simplify statistical approaches to clutter modeling .
- Quantified the uncertainties associated with geoacoustic inversion of reverberation data (Refs [3, 20]). Key result: reverberation predictions have large bias errors (order 10 dB+) even when there has been an REA or survey reverberation measurement and inversion in that same area. Also developed methods for mitigating those errors using one additional observation. This is important because it provides the basis to advance/improve survey reverberation measurements.
- Collaborated with University of Victoria (Jan Dettmer and Stan Dosso) to develop inversion methods for quantifying geoacoustic properties and their uncertainties (Ref [4]). This is important for a) measurement of sediment structures that lead to clutter and b) providing required inputs to validate clutter models.
- Analyzed seabed reflection coherence to estimate sediment geoacoustic properties that are important for modeling reflection and scattering from the seabed (Refs [4, 6]) (with Laurent Guillon, Ecole Navale and PhD student Samuel Pinson)

Measurements:

- Developed measurement method for sediment sound speed lateral variability from seabed bi-static scattering measurements (Ref [16])

- In collaboration with NURC, DRDC-A, NRL, and another PI at ARL-PSU, planned and eonducted the highly successful Clutter09 experiment in the Straits of Sieily.
- Developed engineering design paramcters in collaboration with Peter Nielsen (NURC) for emasurements of seabed refleetion from an AUV. Also used system to measure seabed scattering strength and isolate individual clutter features, confirming hypotheses about the meehamism leading to clutter in areas of submarine mud voleanoes. The elutter meehanism is not the mud volcanoes themselves (of order 100m in lateral spatial extent), but rather small earbonate aeeretions (of order 1-10m in lateral extent and a few meters high) disetributed on the flanks of the mud volcano.

Other:

- Helped organize, with NATO Undersea Research Centre as lead, the International Symposium on Underwater Reverbcration and Clutter Conferenee, Leriei Italy, 9-12 September 2008. This resulted in a eonferenee proeeeding with 43 published papers.
- Scrved on Data Definition Committee for the ONR-PMW/120 Reverberation Workshop II and partieipated in the workshop (Austin, TX, May 2008) including generating energy flux model results for many test eases. The energy flux solutions compare very well with more sophistieated (i.e., eomputationally intensive) models, e.g., coupled mode.

IMPACT/APPLICATIONS

Thc impact of individual aeeomplishments are listed above. Here, they are plaeed in a broader context. Some of the modeling developments appear to be useful for transition to the HiFAST/SAST programs inasmueh as they are extremely computationally effieient. One speeifie example is the elutter or target ccho modeling in whieh realistie fluetuations in the eeho strueture eould be very useful for simulation and training with little computational overhead. Another example is the new theory for propagation in a waveguide with range-dependent boundarics [3], which has potential to speed up point-to-point ealculations by replaeing a range-dependent marehing solution with a range-independent solution using the geometrie mean of the reflection eoefficient and the arithmetie mean of the eyele distanee. For ineoherent models (c.g., ASPM) this could further enhance speed of eomputation, without loss of accuracy.

The AUV measurements have a promising potential for transition to thc survey eommunity to provide seabed refleetion and scattering using a mueh redueed source level (compared to current use), reduction in ship time, reduetion in sensitivity to water eolumn dynamies and also biologies at a mueh higher spatial density.

TRANSITIONS

The seabed scattering data from this program have been transitioned to the PMW-120 Ocean Bottom Charaeterization Initiative (OBCI, Mareus Speekhahn, program manager) for development of a seabed scattering database for the Naval Oeeanographie Offiee. The seattering data have already been kcy to the determination of whieh modeling approach to use for database construetion.

RELATED PROJECTS

This project was part of the Broadband Clutter Initiative Joint Research Project (JRP) including ARL-PSU (USA), DRDC-A (CAN), the NATO Undersea Research Centre (Italy) and NRL-DC (USA). The PI served as leader for the JRP (external to NURC) in collaboration with Peter Nielsen who lead the project within NURC.

PMW-120 OBCI Program: Measurement results and analysis/modeling techniques developed in this program are being transitioned to the design of the first generation Naval Oceanographic Office bottom scattering database.

ONR Applied Reverberation and Modeling Board: that board seeks to enhance transitions of basic research in reverberation modeling to the applied community. Some of the modeling advances developed in this program may transition through the HiFAST FNC to the SAST simulation program.

ONR Quantifying Predicting and Exploiting (QPE) Uncertainty: seabed reflection data measured in this program are being leveraged to QPE for developing/validating methods for quantifying geoacoustic variability and uncertainty.

PUBLICATIONS (Peer Reviewed)

1. Holland, C.W., Incoherent acoustic propagation over a range-dependent seabed, J. Acoust. Soc. Am., 128, 2596-2609, 2010.

2. Holland C.W. and Ellis, D.D., Shallow water reverberation from a sub-bottom interface: a comparison of modeling approaches, J. Comp. Acoust., 17, 29-43, 2009.

3. Holland C.W., Fitting data, but poor predictions: Reverberation prediction uncertainty when seabed parameters are derived from reverberation measurements, J. Acoust. Soc. Am., 2553–2562, 123, 2008.

4. Guillon L., and C.W. Holland, Coherence of signals reflected by the seafloor: numerical modeling vs experimental data, Traitement du signal (French), 25,131-138, 2008.

5. Dettmer J., S.E. Dosso, and C.W. Holland, Joint time/frequency-domain inversion of reflection data for seabed geoacoustic profiles, J. Acoust. Soc. Am., 123, 1306-1317, 2008.

PUBLICATIONS (Conference Proceedings)

6. Pinson, S., L. Guillon, and C.W. Holland, Geoacoustic characterization with an horizontal array by the image source method, European Conference on Underwater Acoustics, Istanbul, 229-236, 2010.

7. Holland C.W., Reverberation and clutter from sub-bottom mechanisms, in International Symposium on Underwater Reverberation and Clutter, edited by P.L. Nielsen, C.H. Harrison, and J-C LeGac, Lerici, Italy, 113-122, Sept. 2008.

8. Abraham D.A. and C.W. Holland, Spatially Compact Clutter, in International Symposium on Underwater Reverberation and Clutter, edited by P.L. Nielsen, C.H. Harrison, and J-C LeGac, Leriei, Italy, 199-208, Sept. 2008.

9. Nielsen P.L., C.W. Harrison, and C.W. Holland, Local bottom characterization using an Autonomous Underwater Vehicle (AUV), in International Symposium on Underwater Reverberation and Clutter, edited by P.L. Nielsen, C.H. Harrison, and J-C LeGac, Leriei, Italy, 345-352, Sept. 2008.

PUBLICATIONS (Conferences, Symposia, and Workshops – abstracts only)

10. Siderius M. and C.W. Holland, Passive seabed remote sensing using ambient noise: Comparisons with active techniques (A), J. Acoust. Soc. Am.,128, 2302, 2010.

11. Dettmer J., Holland C.W., Frequency dependence of attenuation in seabed sediments from Bayesian inference, ECUA Istanbul, 2010.

12. Holland, C.W., Energy Flux insights into effects of a range-dependent seabed on acoustic propagation, David Weston Memorial Work on Sonar Performance Assessment, Cambridge, England, April 2010.

13. Holland, C.W., Energy Flux Predictions for Sonar Assessment Problem A2, David Weston Memorial Work on Sonar Performance Assessment, Cambridge, England, April 2010.

14. Holland, C.W, and P.L. Nielsen, Seabed reflection measurements from an autonomous undersea vehicle: Probing seabed spatial variability, J. Acoust. Soc. Am., 126, 2315, 2009.

15. P. L. Nielsen, C. W. Holland, and R. Hollett, On the use of an autonomous underwater vehicle for seabed characterization. (A), J. Acoust. Soc. Am. 126, 2315, 2009.

16. Holland, C.W, and P.L. Nielsen and R. Hollett, Reverberation and scattering measurements from seabed clutter features using an autonomous undersea vehicle. (A),J. Acoust. Soc. Am. 126 2225, 2009.

17. Goldhahn R., J. Krolik, C. Holland, Waveguide invariant-based characterization of wideband active sonar clutter discretes (A), J. Acoust. Soc. Am., 125, 2704, 2009.

18. Holland C.W., Fine-grained sediment layers: an acoustic lens for sub-bottom sediment processes and structures (A), J. Acoust. Soc. Am., 123, 3084, 2008. (Invited)

19. Nielsen P. and C.W. Holland , Local bottom characterization using an Autonomous Underwater Vehicle (A), J. Acoust. Soc. Am., 123, 3109, 2008.

20. Holland C.W., Fitting data, but poor predictions: Reverberation prediction uncertainty when seabed parameters are derived from reverberation measurements, Technical Metries Workshop, Bay St. Louis, April 2008.